



PLEASE READ ALL INSTRUCTIONS BEFORE USE!

- THIS PRODUCT IS FOR ADULT USE ONLY AND MUST NOT BE OPERATED BY ANYONE UNDER THE AGE OF 18.
- NEVER MODIFY OR ALTER AN AIRSOFT REPLICA. THIS COULD RESULT IN MAKING THE REPLICA UNSAFE AND COULD LEAD TO INJURY OR EVEN DEATH. MODIFICATION WILL ALSO VOID THE WARRANTY.
- ALWAYS BE RESPONSIBLE WITH AIRSOFT REPLICAS, ALWAYS TREAT AIRSOFT REPLICAS WITH THE SAME RESPECT AS A REAL FIREARM.

PRECAUTIONS!

- THIS REPLICA DOES NOT CONTAIN ANY INTERNAL COMPONENTS COMPATIBLE OR INTERCHANGEABLE WITH A REAL FIREARM.
- THIS REPLICA CANNOT ACCEPT FIRING COMPONENTS FROM A REAL FIREARM, NOR BE ABLE TO CHAMBER/FIRE REAL AMMUNITION.
- THIS REPLICA IS DESIGNED TO OPERATE WITH 6MM BB'S. ONLY USE HIGH QUALITY BB'S DESIGNED FOR AIRSOFT.
- NEVER REUSE BB'S THAT HAVE ALREADY BEEN FIRED. THIS CAN CAUSE JAMS AND DAMAGE TO THE REPLICA.
- NEVER USE BB'S THAT ARE DIRTY, DAMP OR WET.
- ALWAYS TRANSPORT REPLICAS IN THE ORIGINAL BOX OR APPROPRIATE CASE. NEVER EVER TRANSPORT A REPLICA IN PLAIN SIGHT.
- ALWAYS STORE AN AIRSOFT REPLICA UNLOADED AND OUT OF REACH OF CHILDREN.
- MODIFYING THE FUNCTION OF THIS REPLICA IN ANYWAY IS UNSAFE AND WILL VOID ANY WARRANTY.
- THE MANUFACTURER, DISTRIBUTORS & RETAILERS ARE NOT LIABLE FOR ANY MALFUNCTION, ACCIDENTS, INJURIES OR REPAIR COSTS RESULTING FROM MISUSE, OR BY DISASSEMBLY AND MODIFICATION OF THIS REPLICA.

SAFETY WARNINGS!

- ALWAYS WEAR SUITABLE EYE AND FACE PROTECTION.
- NEVER POINT AN AIRSOFT REPLICA AT ANYTHING YOU DO NOT INTEND TO SHOOT.
- NEVER SHOOT TARGETS THAT MAY CAUSE A BB TO RICHOCET.
- ENSURE ALL SURROUNDING PEOPLE ARE WEARING SUITABLE EYE AND FACE PROTECTION.
- ALWAYS ENSURE THE REPLICA IS ON SAFE MODE UNTIL YOU INTENDED TO SHOOT.
- ONLY SHOOT THE AIRSOFT REPLICA IN A DESIGNATED AREA TOWARDS A SAFE AREA WITH A BACKSTOP.
- NEVER DIRECTLY LOOK DOWN THE BARREL OF THE REPLICA.

LOADING MAGAZINE

PULL DOWN THE MAGAZINE FOLLOWER TO THE BOTTOM OF THE MAGAZINE.

PLEASE ENSURE NOT TO LET GO OF THE FOLLOWER WHILE PULLED DOWN.

THIS CAN LEAD TO DAMAGE TO FEED LIPS OR FOLLOWER.

HOLD THE MAGAZINE FOLLOWER IN PLACE AND INVERT THE MAGAZINE.

BY HAND OR USING A SPEEDLOADER LOAD THE BB'S THROUGH THE OPENING IN THE MAGAZINE.

ENSURE THAT THE BB'S ARE EQUALLY SPACED WITH NO GAPS TO ENSURE RELIABLE SHOOTING.

LOADING BB'S WITH GAPS CAN LEAD TO MISFIRES FROM THE SMG.

CHARGING SMG

FILL THE MAGAZINE WITH VORSK V6 OR V8 FUEL (TEMP DEPENDENT SEE BELOW)

IF NOT USING V FUEL PLEASE ENSURE YOU USE HIGH QUALITY GREEN GAS WITH SILICONE.

DO NOT FILL WITH OR USE BLACK GAS.

LOAD MAGAZINE INTO THE BOTTOM OF THE SMG UNTIL YOU HEAR/FEEL A CLICK.

TO LOAD AND CHARGE THE SMG PULL THE CHARGING HANDLE BACK AND THEN LET GO, THIS WILL LOAD THE FIRST BB INTO THE HOP CHAMBER READY FOR FIRING. THIS IS ONLY REQUIRED FOR FIRST LOADING OF NEW MAGAZINE.

FITTING SUPPRESSOR

LINE UP THE CUT OUTS AND PUSH THE SUPPRESSOR ONTO THE FLASH HIDER AND TWIST ABOUT 30 DEGREES AND RELEASE. SUPPRESSOR WILL CLICK INTO PLACE.

WARNING - TO REMOVE FLASH HIDER, REMOVE THREE GRUB SCREWS BEFORE UNSCREWING

REMOVING SUPPRESSOR

PUSH SUPPRESSOR TOWARDS THE FLASH HIDER AND TWIST THE SUPPRESSOR 30 DEGREES AND RELEASE. THIS WILL RELEASE THE SUPPRESSOR.

WARNING - SUPPRESSOR CAPS UNDER STRONG SPRING TENSION REMOVE WITH EXTREME CAUTION

FOLDING STOCK

TO FOLD THE STOCK, PULL UP ON THE TUBE OF THE STOCK (HIGHLIGHTED AREA) THEN PULL THE STOCK ROUND TO CLOSED POSITION AND MAKE SURE IT IS LOCKED IN PLACE BY PUSHING DOWN ON HINGE.

HOP UP ADJUSTMENT

TO ADJUST HOP UP OR DOWN, SLOT THE TOOL INTO THE HIGHLIGHTED AREA MATCHING UP THE TEETH. THEN ADJUST UP OR DOWN FOR ADDING OR REMOVING HOP. (SEE +/- ON TOOL)

MAINTENANCE

PLEASE NOTE: IT IS GOOD PRACTICE AND IMPORTANT TO ALWAYS LEAVE A SMALL AMOUNT OF V FUEL (GAS) IN THE MAGAZINES WHEN YOU ARE FINISHED USING THEM.

IT IS ALSO GOOD PRACTICE TO SPRAY A HIGH QUALITY SILICONE SPRAY ONTO THE VALVES AND GAS ROUTER (TOP OF MAGAZINE RUBBER) BEFORE STORAGE.

THIS HELPS TO MAINTAIN PRESURE IN THE MAGAZINE AND KEEP THE SEALS LUBRICATED TO PREVENT LEAKS.

QD STUD ADAPTOR

INSERT A 6MM ALLEN KEY INTO THE QD STUD HOLE AND TURN COUNTER CLOCKWISE TO REMOVE OR CLOCKWISE TO INSTALL. ONCE REMOVED, THIS ALLOWS ACCESS TO A THREAD COMPATIBLE WITH AR BUFFER TUBES/OTHER STOCK OPTIONS.

INSERT THE QD STUD INTO THE BACK OF THE VMP-1 WHILE PRESSING DOWN THE HIGHLIGHTED BUTTON. ONCE IN, RELEASE THE BUTTON AND THE SLING LOOP WILL NOW BE FIXED IN PLACE. PULL THE SLING LOOP TO ENSURE IT IS FULLY SECURE BEFORE USING.

GAS USAGE

VORSK RECOMMENDS THE USE OF VORSK V6/V8 FUEL IN THE VMP-1. PLEASE READ BELOW FOR MORE DETAILS.

TO MAINTAIN PERFORMANCE IN COLDER CONDITIONS (<10°C / 50°F) IT MAY BE REQUIRED TO USE A HIGHER PRESSURE AIRSOFT GAS TO BE USED SUCH AS VORSK V8.

STANDARD CONDITIONS (15°C - 25°C / 59°F - 77°F) WILL REQUIRE STANDARD AIRSOFT "V6/GREEN" GAS IS USED.

DO NOT USE AIRSOFT GAS DESIGNED FOR USE WITH LARGE HEAVY BOLT OPERATED RIFLE REPLICAS OR POWER UP HIGH PRESSURED GAS SUCH AS VORSK V12 OR BLACK GAS AS THIS COULD CAUSE DAMAGE TO INTERNAL MECHANISMS.

SCAN FOR MULTI-LANGUAGE DETAILED MANUALS



FOR MORE DETAILED MANUALS/PARTS DIAGRAMS SCAN HERE AND GO TO MANUALS SECTION OF THE WEBSITE.

MANUALS ALSO AVAILABLE IN MANY OTHER LANGUAGES

